



Features:

- Designed for 24 hour, 7 days a week, high production situations.
- Stainless steel bowl, spiral dough hook, and shaft
- Separate bowl, head and agitator motors
- Has two speeds and reverse function
- Control board has separate timers for 1st and 2nd speed
- Mixer is equipped with built in castors and leveling feet for easy positioning and set-up
- Safety switches protect operator from injury if bowl lid is opened or closed while operator is in the area.
- Powerful belt drive provides low vibration, low noise, and economical maintenance for years of reliable service
- External watertight electrical box

Heavy-Duty Spiral Mixers with Removable Bowl



Models:

☐ *XeTLs880*:

7251b dough capacity heavy-duty spiral mixer with one hook

☐ *XeTLd880*:

7251b dough capacity heavy-duty spiral mixer with two hooks





Standard Accessories:

- Stainless steel bowl
- Electromagnetic hook for bowl
- Easy wheeling dolly for moving up to 880Lbs of dough

Optional Accessories:

• Extra dolly with bowl

Warranty:

• One year, on-site parts and labor

Jarranty Details

The XeIL mixers carry a one-year, on-site parts and labor warranty against any flaws in materials and workmanship. This period begins on the date of the purchase and, provided the unit is used in accordance with our instructions, is in full effect for one year from that date. Any work performed under this warranty must be performed between the hours of 8am and 5pm Monday through Friday. Xebeco will not pay for overtime charges for work performed other then during normal business hours. Damage incurred in transit or from installation error, accident, alteration or misuse is not covered. Xebeco shall not be liable for any consequential compensatory, incidental, or special damages. Contact the Xebeco service department for any warranty claims.

Quality you trust. Experience you know.





Dimensions:

XeTLs880 XeTLd880

A: 60.4" (1535mm) 60.4" (1535mm) **B:** 94.4" (2400mm) 94.4" (2400mm) *C:* 102.3"(2600mm) 102.3"(2600mm)

A: Total mixer width including bowl diameter.

B: Total mixer depth

 \mathcal{C} : Total Mixer Height while head closed

Spiral Motor HP:

1st speed: 35 HP

Bowl Motor HP:

2nd speed: 50 HP

Controls:

1st and 2nd speed: 4 HP

Electrical:

380V/60Hz/3P (Contact factory for alternate voltages)

Control panel with digital timers. Separate timers for

high and low speed. Security key for manual use. Bowl reverse direction switch and head up and down

controls.

Transmission: Heavy duty low noise, low vibration belt drive

Head Lifter Motor HP:

Bowl Guard:

Head lifts open for full access to bowl. Guard must be closed for mixer operation.

Dough Capacity:

XeTLs880: 8801b (330kg)

XeTLd880: 8801b (330kg)

Speeds:

Hook:

1st speed: 95rpm Bowl:

2nd speed: 190rpm 1st speed: 15rpm

Shipping Information:

XeTLs880

XeTLd880

Freight Class:

85

Net Weight:

5,842Lbs (2,650kg) 5,842Lbs (2,650kg)



